

RMC coupling



- Certificate: UL Listed
- Standard: UL 6, NFPA 70
- Material: Carbon steel strip
- Connection: Straight tapped
- Surface: Hot-dip galvanized
- Application: Connect two lengths of RMC

Available size

Trade size	Metric designator	Material	Min length (mm)	Thread	Ref. No.
1/2"	16	Steel	41.3	Straight tapped	C1501 (UL)
3/4"	21	Steel	41.7	Straight tapped	C1502 (UL)
1"	27	Steel	50.0	Straight tapped	C1503 (UL)
1-1/4"	35	Steel	51.6	Straight tapped	C1504 (UL)
1-1/2"	41	Steel	52.4	Straight tapped	C1505 (UL)
2"	53	Steel	54.0	Straight tapped	C1506 (UL)
2-1/2"	63	Steel	81.0	Straight tapped	C1507 (UL)
3"	78	Steel	84.1	Straight tapped	C1508 (UL)
4"	103	Steel	89.3	Straight tapped	C1509 (UL)

RMC nipple



- Certificate: UL Listed
- Standard: UL 6, NFPA 70
- Material: Carbon steel strip
- Connection: NPT, male
- Surface: Hot-dip galvanized
- Application: Short and threaded piece of RMC

Available size

Trade size	Metric designator	Material	Type	Length (mm)	Ref. No.
1/2"	16	Steel	Standard / close / chase	2" ~ 12"	C1521 (UL)
3/4"	21	Steel	Standard / close / chase	2" ~ 12"	C1522 (UL)
1"	27	Steel	Standard / close / chase	2" ~ 12"	C1523 (UL)
1-1/4"	35	Steel	Standard / close / chase	2" ~ 12"	C1524 (UL)
1-1/2"	41	Steel	Standard / close / chase	2" ~ 12"	C1525 (UL)
2"	53	Steel	Standard / close / chase	2" ~ 12"	C1526 (UL)
2-1/2"	63	Steel	Standard / close / chase	2" ~ 12"	C1527 (UL)
3"	78	Steel	Standard / close / chase	2" ~ 12"	C1528 (UL)
4"	103	Steel	Standard / close / chase	2" ~ 12"	C1529 (UL)