


IMC (Intermediate Metal Conduit)

IMC (Intermediate Metal Conduit) is a rigid, medium-walled, threaded raceway manufactured from electric resistance welded (ERW) steel. Serving as a balanced alternative to metallic conduit, it is 25 ~ 40% lighter than RMC and exhibits 20% higher crush resistance than EMT.



- Certificate: UL Listed
- Standard: UL 1242, NFPA 70
- Material: Carbon steel strip
- Connection: NPT, male
- Surface: Hot-dip galvanized



Available size

Trade size	Metric designator	OD	Thickness	Length	Ref. No.
		D (mm)	T (mm)	L (m)	
1/2"	16	20.57 ~ 20.83	1.79 ~ 2.16	3.05 (10 ft)	C1601 (UL)
3/4"	21	26.01 ~ 26.26	1.90 ~ 2.29	3.05 (10 ft)	C1602 (UL)
1"	27	32.64 ~ 32.89	2.16 ~ 2.54	3.05 (10 ft)	C1603 (UL)
1-1/4"	35	41.40 ~ 41.78	2.16 ~ 2.67	3.05 (10 ft)	C1604 (UL)
1-1/2"	41	47.62 ~ 48.01	2.29 ~ 2.79	3.05 (10 ft)	C1605 (UL)
2"	53	59.74 ~ 60.12	2.41 ~ 2.92	3.05 (10 ft)	C1606 (UL)
2-1/2"	63	72.31 ~ 72.82	3.56 ~ 4.06	3.05 (10 ft)	C1607 (UL)
3"	78	88.04 ~ 88.54	3.56 ~ 4.06	3.05 (10 ft)	C1608 (UL)
4"	103	113.18 ~ 113.69	3.56 ~ 4.06	3.05 (10 ft)	C1609 (UL)

Note: Length tolerance: 3.05 m (10 ft) ± 6 mm when a standard coupling is attached.