

IMC coupling



- Certificate: UL Listed
- Standard: UL 1242, NFPA 70
- Material: Carbon steel strip
- Connection: Straight tapped
- Surface: Hot-dip galvanized
- Application: Connect two lengths of IMC

Available size

Trade size	Metric designator	Material	Min length (mm)	Thread	Ref. No.
1/2"	16	Steel	41.3	Straight tapped	C1801 (UL)
3/4"	21	Steel	41.7	Straight tapped	C1802 (UL)
1"	27	Steel	50.0	Straight tapped	C1803 (UL)
1-1/4"	35	Steel	51.6	Straight tapped	C1804 (UL)
1-1/2"	41	Steel	52.4	Straight tapped	C1805 (UL)
2"	53	Steel	54.0	Straight tapped	C1806 (UL)
2-1/2"	63	Steel	81.0	Straight tapped	C1807 (UL)
3"	78	Steel	84.1	Straight tapped	C1808 (UL)
4"	103	Steel	89.3	Straight tapped	C1809 (UL)

IMC nipple



- Certificate: UL Listed
- Standard: UL 1242, NFPA 70
- Material: Carbon steel strip
- Connection: NPT, male
- Surface: Hot-dip galvanized
- Application: Short and threaded piece of IMC

Available size

Trade size	Metric designator	Material	Type	Length (mm)	Ref. No.
1/2"	16	Steel	Standard / close / chase	2" ~ 12"	C1821 (UL)
3/4"	21	Steel	Standard / close / chase	2" ~ 12"	C1822 (UL)
1"	27	Steel	Standard / close / chase	2" ~ 12"	C1823 (UL)
1-1/4"	35	Steel	Standard / close / chase	2" ~ 12"	C1824 (UL)
1-1/2"	41	Steel	Standard / close / chase	2" ~ 12"	C1825 (UL)
2"	53	Steel	Standard / close / chase	4" ~ 12"	C1826 (UL)
2-1/2"	63	Steel	Standard / close / chase	4" ~ 12"	C1827 (UL)
3"	78	Steel	Standard / close / chase	4" ~ 12"	C1828 (UL)
4"	103	Steel	Standard / close / chase	4" ~ 12"	C1829 (UL)