


Rigid PVC conduit

Rigid PVC conduit is a nonmetallic raceway for protecting electrical wires in demanding underground or aboveground installations. Compared to metallic alternatives, rigid PVC conduit offers superior corrosion resistance, excellent electrical insulation, and significantly lighter weight which simplifies handling and installation.



- Certificate: UL Listed
- Standard: UL 651, ASTM D1784, NFPA 70
- Material: PVC, polyvinyl chloride
- Feature: One end belled, impact resistant, sunlight resistant
- Fire rating: UL 94 V-0, self-extinguishing
- Temperature: -40°C to 60°C
- Color: Grey, or customized



Available size (Schedule 40)

Trade size	Metric designator	OD		Thickness Schedule 40		Length L (ft)	Ref. No.
		inch	mm	T (inch)	T (mm)		
1/2"	16	0.840	21.34	0.109	2.77	10 / 20	C2101 (UL)
3/4"	21	1.050	26.67	0.113	2.87	10 / 20	C2102 (UL)
1"	27	1.315	33.40	0.133	3.38	10 / 20	C2103 (UL)
1-1/4"	35	1.660	42.16	0.14	3.56	10 / 20	C2104 (UL)
1-1/2"	41	1.900	48.26	0.145	3.68	10 / 20	C2105 (UL)
2"	53	2.375	60.33	0.154	3.91	10 / 20	C2106 (UL)
2-1/2"	63	2.875	73.03	0.203	5.16	10 / 20	C2107 (UL)
3"	78	3.500	88.90	0.216	5.49	10 / 20	C2108 (UL)
4"	103	4.500	114.30	0.237	6.02	10 / 20	C2109 (UL)
5"	129	5.563	141.30	0.258	6.55	10 / 20	C2110 (UL)
6"	155	6.625	168.28	0.28	7.11	10 / 20	C2111 (UL)

Rigid PVC conduit

Available size (Schedule 80)

Trade size	Metric designator	OD		Thickness Schedule 40		Length L (ft)	Ref. No.
		inch	mm	T (inch)	T (mm)		
1/2"	16	0.840	21.34	0.147	3.73	10 / 20	C2121 (UL)
3/4"	21	1.050	26.67	0.154	3.91	10 / 20	C2122 (UL)
1"	27	1.315	33.40	0.179	4.55	10 / 20	C2123 (UL)
1-1/4"	35	1.660	42.16	0.191	4.85	10 / 20	C2124 (UL)
1-1/2"	41	1.900	48.26	0.200	5.08	10 / 20	C2125 (UL)
2"	53	2.375	60.33	0.218	5.54	10 / 20	C2126 (UL)
2-1/2"	63	2.875	73.03	0.276	7.01	10 / 20	C2127 (UL)
3"	78	3.500	88.90	0.300	7.62	10 / 20	C2128 (UL)
4"	103	4.500	114.30	0.337	8.56	10 / 20	C2129 (UL)
5"	129	5.563	141.30	0.375	9.53	10 / 20	C2130 (UL)
6"	155	6.625	168.28	0.432	10.97	10 / 20	C2131 (UL)