

## Mobile fire extinguisher

Mobile fire extinguisher is mounted on wheels for easy movement. Comparing portable extinguisher, it features bigger extinguishing medium capacity for larger fire protection area, manoeuvred by an operator on foot only.



- Certificate: LPCB / CE Approved
- Standard: BS EN 1866-1
- Fire rating: Class A, B and C fire
- Temperature: -30°C to 60°C (5°C to 60°C for foam)
- W. pressure: 15 bar (150 bar for CO<sub>2</sub>)
- Test: 27 bar (225 bar for CO<sub>2</sub>)
- Surface: Red powder coating



### Main parts and material

|                                   |                                                                  |                             |                                                        |
|-----------------------------------|------------------------------------------------------------------|-----------------------------|--------------------------------------------------------|
| <b>Cart, framing and cylinder</b> | Rugged steel                                                     | <b>Extinguishing medium</b> | ABC powder, AFFF foam, or Carbon dioxide               |
| <b>Control valve</b>              | Brass, with pressure indicator<br>(Not for CO <sub>2</sub> type) | <b>Hose assembly</b>        | Rubber, with hose valve (Not for CO <sub>2</sub> type) |

### Available size

| Type            | Capacity | BSI / LPCB rating | Dimension (mm) |        | Overall weight (kg) | Discharge time (sec.) | Discharge range (m) | Ref. No. |
|-----------------|----------|-------------------|----------------|--------|---------------------|-----------------------|---------------------|----------|
|                 |          |                   | Cylinder dia.  | Height |                     |                       |                     |          |
| ABC powder      | 25 kg    | II B              | 250            | 870    | 40                  | 30                    | 4 ~ 6               | FE8501   |
| ABC powder      | 50 kg    | IV B              | 300            | 1200   | 77                  | 35                    | 4 ~ 6               | FE8502   |
| ABC powder      | 100 kg   | IV B              | 400            | 1200   | 140                 | 35                    | 4 ~ 6               | FE8503   |
| CO <sub>2</sub> | 10 kg    | 144 B             | 152            | 1220   | 46                  | 35                    | 4 ~ 6               | FE8504   |
| CO <sub>2</sub> | 20 kg    | 183 B             | 219            | 1305   | 100                 | 35                    | 4 ~ 6               | FE8505   |
| CO <sub>2</sub> | 30 kg    | 183 B             | 219            | 1590   | 117                 | 35                    | 4 ~ 6               | FE8506   |
| Foam            | 50 L     | IV B              | 300            | 1200   | 77                  | 35                    | 4 ~ 6               | FE8507   |
| Foam            | 100 L    | IV B              | 400            | 1200   | 140                 | 35                    | 4 ~ 6               | FE8508   |