

Threaded pipe nipple (TBE)



· Certificate: ISO

· Surface:

Standard: ASTM A733, BS 3799, GB/T 14383
Material: Forged carbon steel ASTM A105


Forged SS ASTM A182, F304 / F316L

Black painting / hot dip galvanized

Thread: NPT / BSPT for both ends (TBE)
Type: Close type, short type, long type
W. pressure: Equal to same seamless pipe

Pickling white, etc.





Available size for close nipple (Full threaded)

Size			Thickness range		Overall length	Commontion	Def No
NPS	DN	OD (mm)	Sch 40 (STD)	Sch 80 (XS)	L	Connection	Ref. No.
1/2"	15	21.3	2.77	3.73	1-1/8"	TxT	N6201
3/4"	20	26.7	2.87	3.91	1-3/8"	TxT	N6202
1"	25	33.4	3.38	4.55	1-1/2"	TxT	N6203
1-1/4"	32	42.2	3.56	4.85	1-5/8"	TxT	N6204
1-1/2"	40	48.3	3.68	5.08	1-3/4"	TxT	N6205
2"	50	60.3	3.91	5.54	2"	TxT	N6206
2-1/2"	65	73.0	5.16	7.01	2-1/2"	TxT	N6207
3"	80	88.9	5.49	7.62	2-5/8"	TxT	N6208
4"	100	114.3	6.02	8.56	2-7/8"	TxT	N6209
5"	125	141.3	6.55	9.53	3"	TxT	N6210
6"	150	168.3	7.11	10.97	3-1/8"	TxT	N6211

Note:

- 1. The nipple can be made by seamless steel pipe as ASTM A106 / ASTM A312, or welded steel pipe ASTM A53 / ASTM A312.
- 2. Other thickness and length is available as customer request.

















Threaded pipe nipple (TBE)

Available size for short (shoulder) type nipple

Size			Thickness range		Overall length	Commontion	Dof No
NPS	DN	OD (mm)	Sch 40 (STD)	Sch 80 (XS)	L	Connection	Ref. No.
1/2"	15	21.3	2.77	3.73	1-1/2"	TxT	N6221
3/4"	20	26.7	2.87	3.91	2"	TxT	N6222
1"	25	33.4	3.38	4.55	2"	TxT	N6223
1-1/4"	32	42.2	3.56	4.85	2-1/2"	TxT	N6224
1-1/2"	40	48.3	3.68	5.08	2-1/2"	TxT	N6225
2"	50	60.3	3.91	5.54	2-1/2"	TxT	N6226
2-1/2"	65	73.0	5.16	7.01	3"	TxT	N6227
3"	80	88.9	5.49	7.62	3"	TxT	N6228
4"	100	114.3	6.02	8.56	4"	TxT	N6229
5"	125	141.3	6.55	9.53	4-1/2"	TxT	N6230
6"	150	168.3	7.11	10.97	4-1/2"	TxT	N6231

Note

- 1. The nipple can be made by seamless steel pipe as ASTM A106 / ASTM A312, or welded steel pipe ASTM A53 / ASTM A312.
- 2. Other thickness and length is available as customer request.

Available size for long type nipple

Size			Thickness range		Overall length		D (N
NPS	DN	OD (mm)	Sch 40 (STD)	Sch 80 (XS)	L (mm)	Connection	Ref. No.
1/2"	15	21.3	2.77	3.73	50 / 75 /100	TxT	N6241
3/4"	20	26.7	2.87	3.91	50 / 75 /100	TxT	N6242
1"	25	33.4	3.38	4.55	50 / 75 /100	TxT	N6243
1-1/4"	32	42.2	3.56	4.85	75 /100 / 150	TxT	N6244
1-1/2"	40	48.3	3.68	5.08	75 /100 / 150	TxT	N6245
2"	50	60.3	3.91	5.54	75 /100 / 150	TxT	N6246
2-1/2"	65	73.0	5.16	7.01	100 / 150 / 200	TxT	N6247
3"	80	88.9	5.49	7.62	100 / 150 / 200	TxT	N6248
4"	100	114.3	6.02	8.56	100 / 150 / 200	TxT	N6249
5"	125	141.3	6.55	9.53	100 / 150 / 200	TxT	N6250
6"	150	168.3	7.11	10.97	100 / 150 / 200	TxT	N6251

Note:

- 1. The nipple can be made by seamless steel pipe as ASTM A106 / ASTM A312, or welded steel pipe ASTM A53 / ASTM A312.
- 2. Other thickness and length is available as customer request.











