

## Threaded pipe coupling (Merchant coupling)





· Certificate: ISO

· Standard: ASTM A865, ASTM A589,


**ASME B16.11** 


· Material: Forged carbon steel ASTM A105

· Thread: Forged SS ASTM A182, F304 / F316L

· Type: For STD pipe, XS pipe, XXS pipe

· Surface: Black / galvanized





## Available size

Size			Thickness range		D (mm)	Longth type	Dof No
NPS	DN	OD (mm)	Sch 40 (STD)	Sch80 (XS)	D (mm)	Length type	Ref. No.
1/2"	15	21.3	2.77	3.73	27.0	Full / half	N6401
3/4"	20	26.7	2.87	3.91	33.4	Full / half	N6402
1"	25	33.4	3.38	4.55	40.0	Full / half	N6403
1-1/4"	32	42.2	3.56	4.85	48.3	Full / half	N6404
1-1/2"	40	48.3	3.68	5.08	55.9	Full / half	N6405
2"	50	60.3	3.91	5.54	69.8	Full / half	N6406
2-1/2"	65	73.0	5.16	7.01	82.5	Full / half	N6407
3"	80	88.9	5.49	7.62	101.6	Full / half	N6408
4"	100	114.3	6.02	8.56	127.0	Full / half	N6409
5"	125	141.3	6.55	9.53	159.9	Full / half	N6410
6"	150	168.3	7.11	10.97	187.7	Full / half	N6411

## Note

- 1. For half coupling, the unthreaded end is square cut.
- 2. For size up to 2" (DN 50), the coupling is normally supplied with straight tapped NPSC.
- 3. Other thickness and length is available as customer request.













