

Plug type supervisory switch



- Certificate: UL Listed / FM Approved
- Standard: Comply to NFPA 13, 13D, 13R, 72
- Material: PC cover and base, SS bracket
- Contact ratings: Plug: 100mA at 28VDC/AC, 250mA at 12VDC/AC
Cover tamper: 250mA at 28VDC/AC
- Temperature: -40°C to 60°C
- Surface: Corrosion resistant finish



Available size

Valve type	Switch	Cable	Enclosure	Ref. No.
NRS, and others	Single SPDT	2-wire, 18 AWG	NEMA 4X (IP65) and 6P (IP67)	V8201

Supervisory switch (For indicator post and butterfly valve)



- Certificate: UL Listed / FM Approved
- Standard: Comply to NFPA 13, 13D, 13R, 72
- Material: Die cast cover and base
- Contact ratings: 15A at 125/250VAC, 2.5A at 30VDC
- Wiring: Up to 12 AWG wire connection
- Temperature: -40°C to 60°C
- Surface: Corrosion resistant finish



Available size

Valve type	Switch	1/2" Conduit entrances	Enclosure	Ref. No.
Indicator post, and others	Double SPDT	2 knockouts	IP65 and IP67	V8301
Indicator post, and others	Single SPDT	1 knockout	IP67	V8302
Indicator post, and others	Double SPDT	1 knockout	IP67	V8303
Indicator post, and others	Double SPDT with tamper	1 knockout	IP67	V8304

V82-83/