


Direct acting pressure reducing valve



- Certificate: NSF 61
- Standard: NSF 61
- Material: Bronze
- Connection: Thread, NPT / BSPT
- Adjustment: 25 ~ 100 / 30 ~ 95 psi, etc.
- Temperature: Max 70°C, water
- W. pressure: 400 psi
- Surface: Rough bronze



Available size

Size		Pressure adjustment (psi)	A	Connection	Working pressure (psi)	Ref. No.
Inch	DN		mm			
1/2"	15	25 ~ 100 / 80 ~ 150 / 125 ~ 250	143	NPT / BSPT	400	VC3801
3/4"	20	25 ~ 100 / 80 ~ 150 / 125 ~ 250	143	NPT / BSPT	400	VC3802
1"	25	25 ~ 100 / 80 ~ 150 / 125 ~ 250	170	NPT / BSPT	400	VC3803
1-1/4"	32	25 ~ 100 / 75 ~ 160	214	NPT / BSPT	400	VC3804
1-1/2"	40	25 ~ 100 / 75 ~ 160	243	NPT / BSPT	400	VC3805
2"	50	30 ~ 95 / 75 ~ 200	289	NPT / BSPT	400	VC3806
2-1/2"	65	30 ~ 95 / 75 ~ 200	310	NPT / BSPT	400	VC3807