

EMT compression coupling



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Die-cast zinc / carbon steel
- Surface: Electroplating / hot-dip galvanized
- Application: Connect two lengths of EMT

Available size

Trade size	Metric designator	Material	Connection	Ref. No.
1/2"	16	Zinc / steel	Compression + compression	C3601 (UL)
3/4"	21	Zinc / steel	Compression + compression	C3602 (UL)
1"	27	Zinc / steel	Compression + compression	C3603 (UL)
1-1/4"	35	Zinc / steel	Compression + compression	C3604 (UL)
1-1/2"	41	Zinc / steel	Compression + compression	C3605 (UL)
2"	53	Zinc / steel	Compression + compression	C3606 (UL)
2-1/2"	63	Zinc / steel	Compression + compression	C3607 (UL)
3"	78	Zinc / steel	Compression + compression	C3608 (UL)
4"	103	Zinc / steel	Compression + compression	C3609 (UL)

Raintight EMT compression coupling



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Die-cast zinc / carbon steel + rubber sealing ring
- Surface: Electroplating / hot-dip galvanized
- Application: Connect two lengths of EMT in raintight locations

Available size

Trade size	Metric designator	Material	Connection	Ref. No.
1/2"	16	Zinc / steel	Compression + compression	C3621 (UL)
3/4"	21	Zinc / steel	Compression + compression	C3622 (UL)
1"	27	Zinc / steel	Compression + compression	C3623 (UL)
1-1/4"	35	Zinc / steel	Compression + compression	C3624 (UL)
1-1/2"	41	Zinc / steel	Compression + compression	C3625 (UL)
2"	53	Zinc / steel	Compression + compression	C3626 (UL)
2-1/2"	63	Zinc / steel	Compression + compression	C3627 (UL)
3"	78	Zinc / steel	Compression + compression	C3628 (UL)
4"	103	Zinc / steel	Compression + compression	C3629 (UL)