

Watertight conduit hub





· Certificate: UL Listed

· Standard: UL 514B, NFPA 70

Material: Die-cast zincSurface: Electroplating

· Application: Terminate RMC / IMC to box in watertight

locations

Available size

Trade size	Metric designator	Material	Connection	Ref. No.
1/2"	16	Zinc	Thread + thread	C3801 (UL)
3/4"	21	Zinc	Thread + thread	C3802 (UL)
1"	27	Zinc	Thread + thread	C3803 (UL)
1-1/4"	35	Zinc	Thread + thread	C3804 (UL)
1-1/2"	41	Zinc	Thread + thread	C3805 (UL)
2"	53	Zinc	Thread + thread	C3806 (UL)
2-1/2"	63	Zinc	Thread + thread	C3807 (UL)
3"	78	Zinc	Thread + thread	C3808 (UL)
4"	103	Zinc	Thread + thread	C3809 (UL)

Watertight conduit hub with grounding lug





· Certificate: UL Listed

Standard: UL 514B, NFPA 70Material: Die-cast zinc + AL lug

· Surface: Electroplating

· Application: Terminate RMC / IMC to box in watertight

locations, with enhanced grounding

Available size

Trade size	Metric designator	Material	Connection	Ref. No.
1/2"	16	Zinc	Thread + thread	C3821 (UL)
3/4"	21	Zinc	Thread + thread	C3822 (UL)
1"	27	Zinc	Thread + thread	C3823 (UL)
1-1/4"	35	Zinc	Thread + thread	C3824 (UL)
1-1/2"	41	Zinc	Thread + thread	C3825 (UL)
2"	53	Zinc	Thread + thread	C3826 (UL)
2-1/2"	63	Zinc	Thread + thread	C3827 (UL)
3"	78	Zinc	Thread + thread	C3828 (UL)
4"	103	Zinc	Thread + thread	C3829 (UL)











