



Orifice plate

- Certificate: ISO
- Standard: ISO 5167-2, GB 50084
- Material: SS304 / SS316L
- Feature: Simply reduce residual pressure
- Surface: Bright SS surface

Available size

Piping size	Orifice (mm)	Thickness (mm)	Connection	Installation spool	Working pressure (bar)	Ref. No.
DN 50 (2")	12.5 ~ 40	3	Wafer	Yes / no	16	FE7501
DN 65 (2.5")	12.5 ~ 50	3	Wafer	Yes / no	16	FE7502
DN 80 (3")	12.5 ~ 60	3	Wafer	Yes / no	16	FE7503
DN 100 (4")	12.5 ~ 80	6	Wafer	Yes / no	16	FE7504
DN 125 (5")	12.5 ~ 100	6	Wafer	Yes / no	16	FE7505
DN 150 (6")	15 ~ 120	6	Wafer	Yes / no	16	FE7506
DN 200 (8")	20 ~ 160	9	Wafer	Yes / no	16	FE7507
DN 250 (10")	25 ~ 200	9	Wafer	Yes / no	16	FE7508

Note: Orifice size and thickness can be customized.



Fire hose reel cover

- Certificate: ISO
- Standard: Refer to NFPA 701
- Material: Polyester, PVC, etc.
- Feature: Waterproof, dustproof, UV resistant
- Color: Red, gray, yellow, or customized

Available size

Shape	Material	Application	Dimension (mm)	Ref. No.
Round	Polyester + PVC	For fire hose reel max size 1" x 30m, elastic back	630 x 270	FE7601
Door	Flame Retardant PVC	For fire hose reel max size 1" x 30m, hook-and-loop closure	620 x 570 x 230	FE7602

Note: Size, marking and logo can be customized.