

Grounding metallic conduit bushing with insulated throat



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Die-cast zinc / malleable iron + nylon lining + AL lug
- Surface: Electroplating / hot-dip galvanized
- Application: Provide a smooth edge at the termination of RMC/IMC, with enhanced conductor insulation protection and grounding

Available size

Trade size	Metric designator	Material	Connection	Ref. No.
1/2"	16	Zinc / malleable iron	Thread to RMC/IMC	C4141 (UL)
3/4"	21	Zinc / malleable iron	Thread to RMC/IMC	C4142 (UL)
1"	27	Zinc / malleable iron	Thread to RMC/IMC	C4143 (UL)
1-1/4"	35	Zinc / malleable iron	Thread to RMC/IMC	C4144 (UL)
1-1/2"	41	Zinc / malleable iron	Thread to RMC/IMC	C4145 (UL)
2"	53	Zinc / malleable iron	Thread to RMC/IMC	C4146 (UL)
2-1/2"	63	Zinc / malleable iron	Thread to RMC/IMC	C4147 (UL)
3"	78	Zinc / malleable iron	Thread to RMC/IMC	C4148 (UL)
4"	103	Zinc / malleable iron	Thread to RMC/IMC	C4149 (UL)

Plastic conduit bushing



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: PVC
- Surface: smooth, grey color
- Application: Provide a smooth edge at the termination of RMC/IMC

Available size

Trade size	Metric designator	Material	Connection	Ref. No.
1/2"	16	PVC	Thread to RMC/IMC	C4161 (UL)
3/4"	21	PVC	Thread to RMC/IMC	C4162 (UL)
1"	27	PVC	Thread to RMC/IMC	C4163 (UL)
1-1/4"	35	PVC	Thread to RMC/IMC	C4164 (UL)
1-1/2"	41	PVC	Thread to RMC/IMC	C4165 (UL)
2"	53	PVC	Thread to RMC/IMC	C4166 (UL)
2-1/2"	63	PVC	Thread to RMC/IMC	C4167 (UL)
3"	78	PVC	Thread to RMC/IMC	C4168 (UL)
4"	103	PVC	Thread to RMC/IMC	C4169 (UL)