

Reducing bushing



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Carbon steel
- Surface: Hot-dip galvanized
- Application: Connect two pieces of conduit or fittings of different sizes

Available size

Trade size for small diameter	Trade size for large diameter	Material	Connection	Ref. No.
1/2"	3/4" to 2"	Steel	Threaded, F x M	C4201 (UL)
3/4"	1" to 2"	Steel	Threaded, F x M	C4202 (UL)
1"	1-1/4" to 2-1/2"	Steel	Threaded, F x M	C4203 (UL)
1-1/4"	1-1/2" to 2-1/2"	Steel	Threaded, F x M	C4204 (UL)
1-1/2"	2" to 2-1/2"	Steel	Threaded, F x M	C4205 (UL)
2"	2-1/2"	Steel	Threaded, F x M	C4206 (UL)

Three-piece conduit coupling



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Malleable iron / carbon steel
- Surface: Hot-dip galvanized
- Application: Connect two lengths of RMC/IMC that can not be rotated

Available size

Trade size	Metric designator	Material	Connection	Ref. No.
1/2"	16	Malleable iron / steel	Threaded	C4221 (UL)
3/4"	21	Malleable iron / steel	Threaded	C4222 (UL)
1"	27	Malleable iron / steel	Threaded	C4223 (UL)
1-1/4"	35	Malleable iron / steel	Threaded	C4224 (UL)
1-1/2"	41	Malleable iron / steel	Threaded	C4225 (UL)
2"	53	Malleable iron / steel	Threaded	C4226 (UL)
2-1/2"	63	Malleable iron / steel	Threaded	C4227 (UL)
3"	78	Malleable iron / steel	Threaded	C4228 (UL)
4"	103	Malleable iron / steel	Threaded	C4229 (UL)