

Liquid-tight connector



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Die-cast zinc + rubber sealing ring
- Surface: Electroplating
- Application: Terminate LFMC / LFNC to box



Available size

Trade size	Metric designator	Material	Type	Connection	Ref. No.
3/8"	12	Zinc	Straight / 90°	Compression + thread	C5101 (UL)
1/2"	16	Zinc	Straight / 90°	Compression + thread	C5102 (UL)
3/4"	21	Zinc	Straight / 90°	Compression + thread	C5103 (UL)
1"	27	Zinc	Straight / 90°	Compression + thread	C5104 (UL)
1-1/4"	35	Zinc	Straight / 90°	Compression + thread	C5105 (UL)
1-1/2"	41	Zinc	Straight / 90°	Compression + thread	C5106 (UL)
2"	53	Zinc	Straight / 90°	Compression + thread	C5107 (UL)
2-1/2"	63	Zinc	Straight / 90°	Compression + thread	C5108 (UL)
3"	78	Zinc	Straight / 90°	Compression + thread	C5109 (UL)
4"	103	Zinc	Straight / 90°	Compression + thread	C5110 (UL)

Liquid-tight connector with insulated throat



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Die-cast zinc + nylon lining + rubber sealing ring
- Surface: Electroplating
- Application: Terminate LFMC / LFNC to box, with enhanced conductor insulation protection



Available size

Trade size	Metric designator	Material	Type	Connection	Ref. No.
3/8"	12	Zinc	Straight / 90°	Compression + thread	C5121 (UL)
1/2"	16	Zinc	Straight / 90°	Compression + thread	C5122 (UL)
3/4"	21	Zinc	Straight / 90°	Compression + thread	C5123 (UL)
1"	27	Zinc	Straight / 90°	Compression + thread	C5124 (UL)
1-1/4"	35	Zinc	Straight / 90°	Compression + thread	C5125 (UL)
1-1/2"	41	Zinc	Straight / 90°	Compression + thread	C5126 (UL)
2"	53	Zinc	Straight / 90°	Compression + thread	C5127 (UL)
2-1/2"	63	Zinc	Straight / 90°	Compression + thread	C5128 (UL)
3"	78	Zinc	Straight / 90°	Compression + thread	C5129 (UL)
4"	103	Zinc	Straight / 90°	Compression + thread	C5130 (UL)