

Grounding malleable iron liquid-tight connector with insulated throat



- Certificate: ISO
- Standard: UL 514B, NFPA 70
- Material: Malleable iron + nylon lining + rubber sealing ring + AL lug
- Surface: Hot-dip galvanized
- Application: Terminate LFMC / LFNC to box, with enhanced conductor insulation protection and grounding

Available size

Trade size	Metric designator	Material	Type	Connection	Ref. No.
3/8"	12	Malleable iron	Straight / 90° / 45°	Compression + thread	C5241 (ISO)
1/2"	16	Malleable iron	Straight / 90° / 45°	Compression + thread	C5242 (ISO)
3/4"	21	Malleable iron	Straight / 90° / 45°	Compression + thread	C5243 (ISO)
1"	27	Malleable iron	Straight / 90° / 45°	Compression + thread	C5244 (ISO)
1-1/4"	35	Malleable iron	Straight / 90° / 45°	Compression + thread	C5245 (ISO)
1-1/2"	41	Malleable iron	Straight / 90° / 45°	Compression + thread	C5246 (ISO)
2"	53	Malleable iron	Straight / 90° / 45°	Compression + thread	C5247 (ISO)

Nonmetallic liquid-tight connector



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Nylon
- Surface: Smooth, grey color
- Application: Terminate LFNC to box

Available size

Trade size	Metric designator	Material	Type	Connection	Ref. No.
3/8"	12	Nylon	Straight / 90°	Compression + thread	C5301 (UL)
1/2"	16	Nylon	Straight / 90°	Compression + thread	C5302 (UL)
3/4"	21	Nylon	Straight / 90°	Compression + thread	C5303 (UL)
1"	27	Nylon	Straight / 90°	Compression + thread	C5304 (UL)
1-1/4"	35	Nylon	Straight / 90°	Compression + thread	C5305 (UL)
1-1/2"	41	Nylon	Straight / 90°	Compression + thread	C5306 (UL)
2"	53	Nylon	Straight / 90°	Compression + thread	C5307 (UL)

C52-53 /