

Malleable iron liquid-tight connector



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Malleable iron + rubber sealing ring
- Surface: Hot-dip galvanized
- Application: Terminate LFMC / LFNC to box

Available size

Trade size	Metric designator	Material	Type	Connection	Ref. No.
3/8"	12	Malleable iron	Straight / 90° / 45°	Compression + thread	C5201 (UL)
1/2"	16	Malleable iron	Straight / 90° / 45°	Compression + thread	C5202 (UL)
3/4"	21	Malleable iron	Straight / 90° / 45°	Compression + thread	C5203 (UL)
1"	27	Malleable iron	Straight / 90° / 45°	Compression + thread	C5204 (UL)
1-1/4"	35	Malleable iron	Straight / 90° / 45°	Compression + thread	C5205 (UL)
1-1/2"	41	Malleable iron	Straight / 90° / 45°	Compression + thread	C5206 (UL)
2"	53	Malleable iron	Straight / 90° / 45°	Compression + thread	C5207 (UL)

Malleable iron liquid-tight connector with insulated throat



- Certificate: UL Listed
- Standard: UL 514B, NFPA 70
- Material: Malleable iron + nylon lining + rubber sealing ring
- Surface: Hot-dip galvanized
- Application: Terminate LFMC / LFNC to box, with enhanced conductor insulation protection

Available size

Trade size	Metric designator	Material	Type	Connection	Ref. No.
3/8"	12	Malleable iron	Straight / 90° / 45°	Compression + thread	C5221 (UL)
1/2"	16	Malleable iron	Straight / 90° / 45°	Compression + thread	C5222 (UL)
3/4"	21	Malleable iron	Straight / 90° / 45°	Compression + thread	C5223 (UL)
1"	27	Malleable iron	Straight / 90° / 45°	Compression + thread	C5224 (UL)
1-1/4"	35	Malleable iron	Straight / 90° / 45°	Compression + thread	C5225 (UL)
1-1/2"	41	Malleable iron	Straight / 90° / 45°	Compression + thread	C5226 (UL)
2"	53	Malleable iron	Straight / 90° / 45°	Compression + thread	C5227 (UL)