

Threaded conduit body (LR Type) for RMC/IMC



- Certificate: UL Listed
- Standard: UL 514A, NFPA 70
- Material: Aluminum / malleable iron, with cover
- Surface: Powder coated / hot-dip galvanized
- Application: Connect two lengths of RMC/IMC, with access for wire pulling and maintenance

Available size

Trade size	Metric designator	Material	Type	Connection	Ref. No.
1/2"	16	AL / malleable iron	LR	Thread + thread	C5641 (UL)
3/4"	21	AL / malleable iron	LR	Thread + thread	C5642 (UL)
1"	27	AL / malleable iron	LR	Thread + thread	C5643 (UL)
1-1/4"	35	AL / malleable iron	LR	Thread + thread	C5644 (UL)
1-1/2"	41	AL / malleable iron	LR	Thread + thread	C5645 (UL)
2"	53	AL / malleable iron	LR	Thread + thread	C5646 (UL)
2-1/2"	63	AL / malleable iron	LR	Thread + thread	C5647 (UL)
3"	78	AL / malleable iron	LR	Thread + thread	C5648 (UL)
4"	103	AL / malleable iron	LR	Thread + thread	C5649 (UL)

Threaded conduit body (C Type) for RMC/IMC



- Certificate: UL Listed
- Standard: UL 514A, NFPA 70
- Material: Aluminum / malleable iron, with cover
- Surface: Powder coated / hot-dip galvanized
- Application: Connect two lengths of RMC/IMC, with access for wire pulling and maintenance

Available size

Trade size	Metric designator	Material	Type	Connection	Ref. No.
1/2"	16	AL / malleable iron	C	Thread + thread	C5661 (UL)
3/4"	21	AL / malleable iron	C	Thread + thread	C5662 (UL)
1"	27	AL / malleable iron	C	Thread + thread	C5663 (UL)
1-1/4"	35	AL / malleable iron	C	Thread + thread	C5664 (UL)
1-1/2"	41	AL / malleable iron	C	Thread + thread	C5665 (UL)
2"	53	AL / malleable iron	C	Thread + thread	C5666 (UL)
2-1/2"	63	AL / malleable iron	C	Thread + thread	C5667 (UL)
3"	78	AL / malleable iron	C	Thread + thread	C5668 (UL)
4"	103	AL / malleable iron	C	Thread + thread	C5669 (UL)

C56/