

Octagonal junction box



- Certificate: UL Listed
- Standard: UL 514A, UL 50, NFPA 70
- Material: Carbon steel, drawn, with or not grounding screw
- Thickness: Standard 1.6 mm, available 0.8 ~ 1.5 mm
- Surface: Pre-galvanized
- Application: House and protect electrical wiring

Available size

Size	Deep	Capacity	Knockout (KO)		Ref. No.
			Side	Bottom	
4"	1-1/2"	16 cubic inch	4 x 1/2"	5 x 1/2"	C7301 (UL)
4"	1-1/2"	16 cubic inch	4 x 3/4"	3 x 1/2" & 2 x 3/4"	C7302 (UL)
4"	1-1/2"	16 cubic inch	2 x 1/2" & 2 x 3/4"	3 x 1/2" & 2 x 3/4"	C7303 (UL)
4"	2-1/8"	23 cubic inch	4 x 1/2"	5 x 1/2"	C7304 (UL)
4"	2-1/8"	23 cubic inch	4 x 3/4"	3 x 1/2" & 2 x 3/4"	C7305 (UL)
4"	2-1/8"	23 cubic inch	2 x 1/2" & 2 x 3/4"	3 x 1/2" & 2 x 3/4"	C7306 (UL)
4"	2-1/8"	23 cubic inch	4 x 1"	3 x 1/2" & 2 x 3/4"	C7307 (UL)

Octagonal box extension ring



- Certificate: UL Listed
- Standard: UL 514A, UL 50, NFPA 70
- Material: Carbon steel, drawn
- Thickness: Standard 1.6 mm, available 0.8 ~ 1.5 mm
- Surface: Pre-galvanized
- Application: Extend depth of existing octagonal junction box

Available size

Size	Deep	Capacity	Knockout (KO)		Ref. No.
			Side	Bottom	
4"	1-1/2"	16 cubic inch	4 x 1/2"	/	C7321 (UL)
4"	1-1/2"	16 cubic inch	4 x 3/4"	/	C7322 (UL)
4"	1-1/2"	16 cubic inch	2 x 1/2" & 2 x 3/4"	/	C7323 (UL)
4"	2-1/8"	23 cubic inch	4 x 1/2"	/	C7324 (ISO)
4"	2-1/8"	23 cubic inch	4 x 3/4"	/	C7325 (ISO)
4"	2-1/8"	23 cubic inch	2 x 1/2" & 2 x 3/4"	/	C7326 (ISO)
4"	2-1/8"	23 cubic inch	4 x 1"	/	C7327 (ISO)