

Vertical tee down



- Certificate: ISO
- Standard: NEMA VE 1, NFPA 70
- Material: Carbon steel / stainless steel
- Thickness: Standard 1.0 mm, available 1.2 ~ 2.0 mm
- Feature: Vertical, different bend radius
- Surface: Hot-dip galvanized, pre-galvanized / mill finish, polished

Available size

Size	Material	Bottom	Width (mm)	Height (mm)	Bend radius (mm)	Ref. No.
50 x 50	CS / SS	Solid / ventilated	50	50	100	C8701 (ISO)
75 x 50	CS / SS	Solid / ventilated	75	50	150	C8702 (ISO)
75 x 75	CS / SS	Solid / ventilated	75	75	150	C8703 (ISO)
100 x 50	CS / SS	Solid / ventilated	100	50	150	C8704 (ISO)
100 x 75	CS / SS	Solid / ventilated	100	75	150	C8705 (ISO)
100 x 100	CS / SS	Solid / ventilated	100	100	150	C8706 (ISO)
150 x 50	CS / SS	Solid / ventilated	150	50	150	C8707 (ISO)
150 x 75	CS / SS	Solid / ventilated	150	75	150	C8708 (ISO)
150 x 100	CS / SS	Solid / ventilated	150	100	150	C8709 (ISO)
150 x 150	CS / SS	Solid / ventilated	150	150	150	C8710 (ISO)
200 x 50	CS / SS	Solid / ventilated	200	50	150	C8711 (ISO)
200 x 75	CS / SS	Solid / ventilated	200	75	150	C8712 (ISO)
200 x 100	CS / SS	Solid / ventilated	200	100	150	C8713 (ISO)
200 x 150	CS / SS	Solid / ventilated	200	150	150	C8714 (ISO)
200 x 200	CS / SS	Solid / ventilated	200	200	150	C8715 (ISO)
300 x 50	CS / SS	Solid / ventilated	300	50	150	C8716 (ISO)
300 x 75	CS / SS	Solid / ventilated	300	75	150	C8717 (ISO)
300 x 100	CS / SS	Solid / ventilated	300	100	150	C8718 (ISO)
300 x 150	CS / SS	Solid / ventilated	300	150	150	C8719 (ISO)
300 x 200	CS / SS	Solid / ventilated	300	200	150	C8720 (ISO)
400 x 50	CS / SS	Solid / ventilated	400	50	150 / 300	C8721 (ISO)

Vertical tee down

Available size

Size	Material	Bottom	Width (mm)	Height (mm)	Bend radius (mm)	Ref. No.
400 x 75	CS / SS	Solid / ventilated	400	75	150 / 300	C8722 (ISO)
400 x 100	CS / SS	Solid / ventilated	400	100	150 / 300	C8723 (ISO)
400 x 150	CS / SS	Solid / ventilated	400	150	150 / 300	C8724 (ISO)
400 x 200	CS / SS	Solid / ventilated	400	200	150 / 300	C8725 (ISO)
500 x 50	CS / SS	Solid / ventilated	500	50	150 / 300	C8726 (ISO)
500 x 75	CS / SS	Solid / ventilated	500	75	150 / 300	C8727 (ISO)
500 x 100	CS / SS	Solid / ventilated	500	100	150 / 300	C8728 (ISO)
500 x 150	CS / SS	Solid / ventilated	500	150	150 / 300	C8729 (ISO)
500 x 200	CS / SS	Solid / ventilated	500	200	150 / 300	C8730 (ISO)
600 x 50	CS / SS	Solid / ventilated	600	50	150 / 300 / 600	C8731 (ISO)
600 x 75	CS / SS	Solid / ventilated	600	75	150 / 300 / 600	C8732 (ISO)
600 x 100	CS / SS	Solid / ventilated	600	100	150 / 300 / 600	C8733 (ISO)
600 x 150	CS / SS	Solid / ventilated	600	150	150 / 300 / 600	C8734 (ISO)
600 x 200	CS / SS	Solid / ventilated	600	200	150 / 300 / 600	C8735 (ISO)