Vertical tee up

- · Certificate: ISO
- · Standard: NEMA VE 1, NFPA 70
- · Material: Carbon steel / stainless steel
- · Thickness: Standard 1.0 mm, available 1.2 ~ 2.0 mm
- · Feature: Vertical, different bend radius
- · Surface: Hot-dip galvanized, pre-galvanized / mill finish, polished

Available size

Size	Material	Bottom	Width (mm)	Height (mm)	Bend radius (mm)	Ref. No.
50 x 50	CS / SS	Solid / ventilated	50	50	100	C8801 (ISO)
75 x 50	CS / SS	Solid / ventilated	75	50	150	C8802 (ISO)
75 x 75	CS / SS	Solid / ventilated	75	75	150	C8803 (ISO)
100 x 50	CS / SS	Solid / ventilated	100	50	150	C8804 (ISO)
100 x 75	CS / SS	Solid / ventilated	100	75	150	C8805 (ISO)
100 x 100	CS / SS	Solid / ventilated	100	100	150	C8806 (ISO)
150 x 50	CS / SS	Solid / ventilated	150	50	150	C8807 (ISO)
150 x 75	CS / SS	Solid / ventilated	150	75	150	C8808 (ISO)
150 x 100	CS / SS	Solid / ventilated	150	100	150	C8809 (ISO)
150 x 150	CS / SS	Solid / ventilated	150	150	150	C8810 (ISO)
200 x 50	CS / SS	Solid / ventilated	200	50	150	C8811 (ISO)
200 x 75	CS / SS	Solid / ventilated	200	75	150	C8812 (ISO)
200 x 100	CS / SS	Solid / ventilated	200	100	150	C8813 (ISO)
200 x 150	CS / SS	Solid / ventilated	200	150	150	C8814 (ISO)
200 x 200	CS / SS	Solid / ventilated	200	200	150	C8815 (ISO)
300 x 50	CS / SS	Solid / ventilated	300	50	150	C8816 (ISO)
300 x 75	CS / SS	Solid / ventilated	300	75	150	C8817 (ISO)
300 x 100	CS / SS	Solid / ventilated	300	100	150	C8818 (ISO)
300 x 150	CS / SS	Solid / ventilated	300	150	150	C8819 (ISO)
300 x 200	CS / SS	Solid / ventilated	300	200	150	C8820 (ISO)
400 x 50	CS / SS	Solid / ventilated	400	50	150 / 300	C8821 (ISO)

Vertical tee up

Available size

Size	Material	Bottom	Width (mm)	Height (mm)	Bend radius (mm)	Ref. No.
400 x 75	CS / SS	Solid / ventilated	400	75	150 / 300	C8822 (ISO)
400 x 100	CS / SS	Solid / ventilated	400	100	150 / 300	C8823 (ISO)
400 x 150	CS / SS	Solid / ventilated	400	150	150 / 300	C8824 (ISO)
400 x 200	CS / SS	Solid / ventilated	400	200	150 / 300	C8825 (ISO)
500 x 50	CS / SS	Solid / ventilated	500	50	150 / 300	C8826 (ISO)
500 x 75	CS / SS	Solid / ventilated	500	75	150 / 300	C8827 (ISO)
500 x 100	CS / SS	Solid / ventilated	500	100	150 / 300	C8828 (ISO)
500 x 150	CS / SS	Solid / ventilated	500	150	150 / 300	C8829 (ISO)
500 x 200	CS / SS	Solid / ventilated	500	200	150 / 300	C8830 (ISO)
600 x 50	CS / SS	Solid / ventilated	600	50	150 / 300 / 600	C8831 (ISO)
600 x 75	CS / SS	Solid / ventilated	600	75	150 / 300 / 600	C8832 (ISO)
600 x 100	CS / SS	Solid / ventilated	600	100	150 / 300 / 600	C8833 (ISO)
600 x 150	CS / SS	Solid / ventilated	600	150	150 / 300 / 600	C8834 (ISO)
600 x 200	CS / SS	Solid / ventilated	600	200	150 / 300 / 600	C8835 (ISO)