


Fixed fire hose reel (Automatic)

Fixed fire hose reel is normally installed in a building for the occupants to extinguish a small fire. It could not swing. For automatic type, rotation of the reel opens the valve automatically to release water.



- Certificate: LPCB / CE Approved
- Standard: BS EN 671-1
- W. pressure: 12 bar
- Test / burst: 18 bar / 30 bar
- Hose color: Red or black
- Surface: Red powder coating (RAL 3000)



Main parts and material

Semi-rigid hose	PVC tubing as EN 694	Shut-off nozzle	Nylon or brass, rotary operated jet / spray
Reel	Carbon steel or SS to two side plates (disc), brass waterway	Inlet stop valve 1" brass	Standard: Ball valve, lever operated; Optional: Gate valve, handwheel or lockshield

Available size

Size	Hose bore (mm)	Hose length (m)	Nozzle material	Nozzle size (mm)	Overall size H x W x D (mm)	Ref. No.
19 x 30, 3/4"	19	30	Nylon	6	720 x 555 x 240	FE6101
19 x 30, 3/4"	19	30	Brass	6	720 x 555 x 240	FE6102
25 x 30, 1"	25	30	Nylon	7	720 x 555 x 270	FE6103
25 x 30, 1"	25	30	Brass	8	720 x 555 x 270	FE6104

Note:

1. It is wall mounted only.
2. A rectangular shaped wall mounting bracket is pre-assembled, together with a holder wheel for easy operation.
3. It is also available to add a pressure gauge, which can be located in the middle of the disc or at the inlet of stop valve.

FE61 /