


## Flanged straight tee (Equal tee)



- Certificate: ISO
- Standard: Refer to ANSI / UL 213C, EN 1092
- Material: Ductile iron
- Flanged end: EN 1092-2, PN10 / PN 16 / PN 25, RF or ANSI B16.1 Class 125, B16.42 Class 150, FF or RF
- Rated pressure: 300 ~ 500 psi
- Surface: Red or blue painting



### Available size

| Inch | Size |       | Center to end | Ref. No. |
|------|------|-------|---------------|----------|
|      | DN   | mm    | L (mm)        |          |
| 3"   | 80   | 88.9  | 165           | U3501    |
| 4"   | 100  | 114.3 | 180           | U3502    |
| 6"   | 150  | 165.1 | 220           | U3503    |
| 8"   | 200  | 219.1 | 260           | U3504    |
| 10"  | 250  | 273.0 | 350           | U3505    |
| 12"  | 300  | 323.9 | 400           | U3506    |
| 14"  | 350  | 355.6 | 425           | U3507    |
| 16"  | 400  | 406.4 | 450           | U3508    |
| 18"  | 450  | 457.2 | 475           | U3509    |
| 20"  | 500  | 508   | 500           | U3510    |
| 24"  | 600  | 609.6 | 550           | U3511    |