

Sprinkler air compressor



- Certificate: ISO
- Standard: Refer to NFPA 13, UL 1450
- Material: Carbon steel
- Feature: Low noise, low Amp draw, high efficiency motor
- Surface: White painted

Available size

Power (HP)	Voltage (V)	Speed (RPM)	Capacity (CFM)	Working pressure (psi)	Outlet	Dimension L x W x H (mm)	Ref. No.
0.75	110 / 220	1450	3.3	72.5	1/4", G	457 x 381 x 381	V9201
1.2	110 / 220	1450	4	72.5	1/4", G	457 x 381 x 381	V9202

Dry pilot actuator



- Certificate: UL Listed / FM Approved
- Standard: Refer to UL 260, FM 1011/1012/1013
- Material: Bronze body and cover, Nylon diaphragm
- Function: Auxiliary releasing device for deluge and preaction valve
- W. pressure: 250 psi, water, etc.
- Surface: Rough bronze

Available size

Inlet	Pilot line connection	Outlet to drain	Inlet water pressure	Air (Nitrogen) pressure	Ref. No.
1/2" NPT	1/2" NPT	1/2" NPT	250 psi	50 psi	V9301 (UL/FM)

Note: It is UL/FM certified when used with specific deluge valve and preaction valve.