

## Sprinkler air compressor



- Certificate: ISO
- Standard: Refer to NFPA 13, UL 1450
- Material: Carbon steel
- Feature: Low noise, low Amp draw, high efficiency motor
- Surface: White painted

### Available size

| Power (HP) | Voltage (V) | Speed (RPM) | Capacity (CFM) | Working pressure (psi) | Outlet  | Dimension L x W x H (mm) | Ref. No. |
|------------|-------------|-------------|----------------|------------------------|---------|--------------------------|----------|
| 0.75       | 110 / 220   | 1450        | 3.3            | 72.5                   | 1/4", G | 457 x 381 x 381          | V9201    |
| 1.2        | 110 / 220   | 1450        | 4              | 72.5                   | 1/4", G | 457 x 381 x 381          | V9202    |

## Dry pilot actuator



- Certificate: UL Listed / FM Approved
- Standard: Refer to UL 260, FM 1011/1012/1013
- Material: Bronze body and cover, Nylon diaphragm
- Function: Auxiliary releasing device for deluge and preaction valve
- W. pressure: 250 psi, water, etc.
- Surface: Rough bronze

### Available size

| Inlet    | Pilot line connection | Outlet to drain | Inlet water pressure | Air (Nitrogen) pressure | Ref. No.      |
|----------|-----------------------|-----------------|----------------------|-------------------------|---------------|
| 1/2" NPT | 1/2" NPT              | 1/2" NPT        | 250 psi              | 50 psi                  | V9301 (UL/FM) |

**Note:** It is UL/FM certified when used with specific deluge valve and preaction valve.