

Ceiling / wall mount sounder strobe (NFPA 72)

Ceiling / wall mount sounder strobe is a fire alarm notification appliance to provide synchronized audible and visual alerts during fire emergency, so to warn on-site personnel to take appropriate measure.



- Certificate: UL Listed
- Standard: UL 464, UL 1638, UL 1971, NFPA 72, NFPA 70
- Feature: Field-adjustable for sound and strobe output
- Material: ABS cover, red or white
- Temperature: 0°C to 49°C
- Humidity: 0% to 93%, non-condensing
- Installation: Indoor, ceiling or wall mounting

Available size

Operating voltage	Alarm current	Sound output	Strobe light	Dimension Dia x H (mm)	Enclosure color	Ref. No.
24 VDC or VFWR	≤ 0.37 A @ 95 cd	> 78 dB(A) @ 10 ft	15 / 30 / 75 / 95 cd	170 x 55	Red	A3101 (UL)
24 VDC or VFWR	≤ 0.37 A @ 95 cd	> 78 dB(A) @ 10 ft	15 / 30 / 75 / 95 cd	170 x 55	White	A3102 (UL)

Wall mount sounder strobe (NFPA 72)

Wall mount sounder strobe is a fire alarm notification appliance to provide synchronized audible and visual alerts during fire emergency, so to warn on-site personnel to take appropriate measure.



- Certificate: UL Listed
- Standard: UL 464, UL 1638, UL 1971, NFPA 72, NFPA 70
- Feature: Field-adjustable for sound and strobe output
- Material: ABS cover, red or white
- Temperature: 0°C to 49°C
- Humidity: 0% to 93%, non-condensing
- Installation: Indoor, wall mounting

Available size

Operating voltage	Alarm current	Sound output	Strobe light	Dimension W x H x D (mm)	Enclosure color	Ref. No.
24 VDC or VFWR	≤ 0.34 A @ 110 cd	> 79 dB(A) @ 10 ft	15 / 30 / 75 / 110 cd	68 x 113 x 21	Red	A3201 (UL)
24 VDC or VFWR	≤ 0.34 A @ 110 cd	> 79 dB(A) @ 10 ft	15 / 30 / 75 / 110 cd	68 x 113 x 21	White	A3202 (UL)