

Wall mount sounder (NFPA 72)

Wall mount sounder is a fire alarm notification appliance to provide audible alert during fire emergency, so to warn on-site personnel to take appropriate measure.



- Certificate: UL Listed
- Standard: UL 464, UL 1638, UL 1971, NFPA 72, NFPA 70
- Feature: Field-adjustable for sound output
- Material: ABS cover, red or white
- Temperature: 0°C to 49°C
- Humidity: 0% to 93%, non-condensing
- Installation: Indoor, wall mounting

Available size

Operating voltage	Alarm current	Sound output	Strobe light	Dimension W x H x D (mm)	Enclosure color	Ref. No.
24 VDC or VFWR	< 0.04 A	> 79 dB(A) @ 10 ft	/	68 x 113 x 21	Red	A3301 (UL)
24 VDC or VFWR	< 0.04 A	> 79 dB(A) @ 10 ft	/	68 x 113 x 21	White	A3302 (UL)

Wall mount strobe (NFPA 72)

Wall mount strobe is a fire alarm notification appliance to provide visual alerts during fire emergency, so to warn on-site personnel to take appropriate measure.



- Certificate: UL Listed
- Standard: UL 464, UL 1638, UL 1971, NFPA 72, NFPA 70
- Feature: Field-adjustable for strobe output
- Material: ABS cover, red or white
- Temperature: 0°C to 49°C
- Humidity: 0% to 93%, non-condensing
- Installation: Indoor, wall mounting

Available size

Operating voltage	Alarm current	Sound output	Strobe light	Dimension W x H x D (mm)	Enclosure color	Ref. No.
24 VDC or VFWR	≤ 0.31 A @ 110 cd	/	15 / 30 / 75 / 110 cd	68 x 113 x 21	Red	A3401 (UL)
24 VDC or VFWR	≤ 0.31 A @ 110 cd	/	15 / 30 / 75 / 110 cd	68 x 113 x 21	White	A3402 (UL)