

Ceiling mount horn/strobe (NFPA 72)

Ceiling mount strobe is a fire alarm notification appliance to provide synchronized audible and visual alerts during fire emergency, so to warn on-site personnel to take appropriate measure.



- Certificate: UL Listed / FM Approved
- Standard: UL 464, UL 1638, UL 1971, NFPA 72, NFPA 70
- Feature: Field-adjustable for sound and strobe output
- Material: ABS cover, red or white
- Temperature: 0°C to 50°C
- Humidity: 0% to 93%, non-condensing
- Installation: Indoor, ceiling mounting

Available size

Operating voltage	Alarm current	Sound output	Strobe light	Dimension W x H x D (mm)	Enclosure color	Ref. No.
24 VDC or VFWR	227 mA @ 110 cd	> 81 dB(A) @ 10 ft	15 / 30 / 75 / 110 cd	123 x 123 x 44	Red	A4111 (UL/FM)
24 VDC or VFWR	227 mA @ 110 cd	> 81 dB(A) @ 10 ft	15 / 30 / 75 / 110 cd	123 x 123 x 44	White	A4112 (UL/FM)

Wall mount horn/strobe (NFPA 72)

Wall mount horn/strobe is a fire alarm notification appliance to provide synchronized audible and visual alerts during fire emergency, so to warn on-site personnel to take appropriate measure.



- Certificate: UL Listed / FM Approved
- Standard: UL 464, UL 1638, UL 1971, NFPA 72, NFPA 70
- Feature: Field-adjustable for sound and strobe output
- Material: ABS cover, red or white
- Temperature: 0°C to 50°C
- Humidity: 0% to 93%, non-condensing
- Installation: Indoor, wall mounting

Available size

Operating voltage	Alarm current	Sound output	Strobe light	Dimension W x H x D (mm)	Enclosure color	Ref. No.
24 VDC or VFWR	180 mA @ 185 cd	> 81 dB(A) @ 10 ft	15 / 30 / 75 / 110 / 185 cd	123 x 123 x 50	Red	A4211 (UL/FM)
24 VDC or VFWR	180 mA @ 185 cd	> 81 dB(A) @ 10 ft	15 / 30 / 75 / 110 / 185 cd	123 x 123 x 50	White	A4212 (UL/FM)