

Handheld programmer (EN 54)

Handheld programmer is a compact and on-site programming tool for EN 54 series fire equipment. It is used to write, read and erase device parameters such as address, sensitivity, mode and type, so to meet the site situation.



- Certificate: ISO
- Standard: Refer to EN 54
- Feature: LED display, functional keys, pluggable cable with clips
- Material: ABS housing, white
- Temperature: -10°C to 50°C
- Humidity: 0% to 95%, non-condensing

Available size

Power	Standby current	Working current	Dimension W x H x D (mm)	Ref. No.
2 x 1.5 AA battery, or Micro-USB Link	0.0 µA	3.0 mA	60 x 135 x 30	AE0601 (ISO)

Note: For battery, it needs to be purchased separately.

Intelligent power supply unit (EN 54, PSU)

Intelligent power supply unit (PSU) is used to supply power to on-site fire equipment. It converts AC input to DC 24V output, and it features backup power supply and charging capability to ensure uninterrupted operation.



- Certificate: ISO
- Standard: EN 54-4
- Feature: Addressable, LED indicator, digital display
- Material: Steel sheet cabinet, grey
- Temperature: -10°C to 50°C
- Humidity: 0% to 95%, non-condensing
- Installation: Wall mounting

Available size

Type	Main input power	Backup power	Output power	Power switching time	Dimension W x H x D (mm)	Ref. No.
PSU 5A	100 to 240 VAC, 133 W	24V, 12Ah	24 VDC, 5A	No delay	380 x 450 x 135	AE0701 (ISO)
PSU 10A	100 to 240 VAC, 265 W	24V, 12Ah	24 VDC, 10A	No delay	380 x 450 x 135	AE0702 (ISO)

Note: For backup power, it is recommended to use sealed lead acid battery which needs to be purchased separately.