

Addressable sounder beacon base (EN 54)

Addressable sounder beacon base integrates with a fire detector to identify fire and alert on-site personnel, or functions as a standalone 2-wire audio and visual fire alarm notification device. It reduces the cost and time of installation.



- Certificate: LPCB approved
- Standard: EN 54-3
- Feature: Addressable, pre-alarm / evacuation
- Material: ABS housing, white
- Temperature: -10°C to 50°C
- Humidity: 0% to 95%, non-condensing
- Installation: Combined or standalone


Available size

Operating voltage	Standby current	Alarm current	Sound output	Strobe light	Dimension Dia x H (mm)	Ref. No.
24 VDC	≤ 0.8 mA	≤ 5.0 mA	17 tones	8 highlight LED	140 x 59	AE3301 (LPCB)

Note: For installation, it can either be mounted in combination with a fire detector (With base), or installed as a standalone unit with cover.

Addressable sounder base (EN 54)

Addressable sounder base integrates with a fire detector to identify fire and alert on-site personnel, or functions as a standalone 2-wire audio fire alarm notification device. It reduces the cost and time of installation.



- Certificate: ISO
- Standard: EN 54-3
- Feature: Addressable, pre-alarm / evacuation
- Material: ABS housing, white
- Temperature: -10°C to 50°C
- Humidity: 0% to 95%, non-condensing
- Installation: Combined or standalone

Available size

Operating voltage	Standby current	Alarm current	Sound output	Strobe light	Dimension Dia x H (mm)	Ref. No.
24 VDC	≤ 0.8 mA	≤ 4.0 mA	17 tones	/	140 x 59	AE3401 (LPCB)

Note: For installation, it can either be mounted in combination with a fire detector (With base), or installed as a standalone unit with cover.