

## Waterproof enclosure for fire detector (EN 54)

Waterproof enclosure for fire detector provides IP33 protection to ensure reliable operation of combined fire detector in harsh installation, such as outdoor, tunnel, and other humid or dusty locations.



- Certificate: ISO
- Standard: Refer to EN 54
- Feature: Waterproof, for fire detector
- Material: ABS base, rubber pad
- Temperature: -40°C to 70°C
- Protection: Outdoor use, IP33

### Available size

Application	Dimension Dia x H (mm)	Ref. No.
Waterproof for smoke detector, heat detector, multi-sensor detector	139 x 65	AE3701 (ISO)

## Waterproof enclosure for manual call point (EN 54)

Waterproof enclosure for manual call point provides IP66 protection to ensure reliable operation of combined manual call point in harsh installation, such as outdoor, tunnel, coastal facility and other high humid or dusty locations.



- Certificate: ISO
- Standard: Refer to EN 54
- Feature: Waterproof, for manual call point or module
- Material: ABS base, PC transparent cover
- Temperature: -40°C to 70°C
- Protection: Outdoor use, IP66

### Available size

Application	Dimension W x H x D (mm)	Ref. No.
Waterproof for manual call point, module, etc.	145 x 182 x 105	AE3711 (ISO)

AE37 /