

## Wireless sounder strobe

Wireless sounder strobe is a non-wired fire alarm notification device to provide synchronized audible and visual alerts during fire emergency, so to warn on-site personnel to take appropriate measure.



- Certificate: ISO
- Standard: GB 22370
- Feature: Foslink wireless, highlight LED
- Material: ABS cover, red and white
- Temperature: -10°C to 55°C
- Humidity: 0% to 95%, non-condensing
- Installation: Wall or ceiling mounting



### Available size

Operating voltage	Alarm current	Sound output	Flashing frequency	Wireless communication	Dimension Dia x H (mm)	Ref. No.
3V, battery	< 40 mA	75 ~ 100 dB @ 3m	1.1 ~ 1.8 Hz	Max 300 m	100 x 48	AE6601 (ISO)

**Note:** For power supply, it is built-in 2 x 1.5 AA lithium batteries.

## Standalone gas detector

Standalone gas detector monitors Methane CH<sub>4</sub> concentration. Upon reaching the threshold, it initiates audible and visual alarms, while simultaneously triggering a fail-safe relay to actuate emergency shut-off valve.



- Certificate: ISO
- Standard: GB 22370, GB 15322.2
- Feature: Audible and visual alarms
- Material: ABS housing, white
- Temperature: -10°C to 55°C
- Humidity: 0% to 95%, non-condensing
- Installation: Wall mounting



### Available size

Operating voltage	Monitor status	Alarm status	Detection gas	Output control	Dimension W x H x D (mm)	Ref. No.
220 VAC, 50 Hz	≤ 2.0 W	< 2.5 mA	Methane, 0 ~ 20% LEL	2, active + passive	85 x 85 x 35	AE6701 (ISO)

**Note:** It can be added an extra IOT communication chip (LoRa wireless protocol), so to network with control panel.