


## Strut channel flat fittings



- Certificate: ISO
- Standard: UL 5B, NFPA 70
- Material: Carbon steel or stainless steel
- Feature: Flat plate design with 1 to 7 holes to suit splicing, T-joints, and reinforcement needs
- Surface: CS, zinc electroplated / hot-dip galvanized  
SS, mill finish / passivated

### Available size

Size		Bolting hole	Shape	Material	Ref. No.
Imperial	Metric				
1/4"	M6	1-hole, 2-hole, etc.	Square, rectangular, etc.	CS / SS	C9801 (ISO)
5/16"	M8	1-hole, 2-hole, etc.	Square, rectangular, etc.	CS / SS	C9802 (ISO)
3/8"	M10	1-hole, 2-hole, etc.	Square, rectangular, etc.	CS / SS	C9803 (ISO)
1/2"	M12	1-hole, 2-hole, etc.	Square, rectangular, etc.	CS / SS	C9804 (ISO)
5/8"	M16	1-hole, 2-hole, etc.	Square, rectangular, etc.	CS / SS	C9805 (ISO)

**Note:** It is available in square (1-5/8" x 1-5/8", 1-hole), rectangular (e.g., 3-1/4" x 1-5/8" with 2 holes, 4-7/8" x 1-5/8" with 3 holes), and other shapes.

## Strut channel angle fittings



- Certificate: ISO
- Standard: UL 5B, NFPA 70
- Material: Carbon steel or stainless steel
- Feature: Angle plate design with 1 to 7 holes for flexible splicing, T-joints, corner bracing, and reinforcement in strut framing.
- Surface: CS, zinc electroplated / hot-dip galvanized  
SS, mill finish / passivated

### Available size

Size		Bolting hole	Shape	Material	Ref. No.
Imperial	Metric				
1/4"	M6	2-hole, 3-hole, etc.	L, T, etc.	CS / SS	C9811 (ISO)
5/16"	M8	2-hole, 3-hole, etc.	L, T, etc.	CS / SS	C9812 (ISO)
3/8"	M10	2-hole, 3-hole, etc.	L, T, etc.	CS / SS	C9813 (ISO)
1/2"	M12	2-hole, 3-hole, etc.	L, T, etc.	CS / SS	C9814 (ISO)
5/8"	M16	2-hole, 3-hole, etc.	L, T, etc.	CS / SS	C9815 (ISO)

**Note:** It is available in L (e.g., 2-1/16" x 1-7/8" x 1-5/8" with 2 holes, 3-1/2" x 2-1/4" x 1-5/8" with 3 holes), T, and other shapes.