


## Intelligent waterproof non-maintained emergency light (2 adjustable heads)

Intelligent waterproof non-maintained emergency light (2 adjustable heads) integrates with a central monitoring system via its built-in networking interface, providing customizable illumination coverage during power outages. This classic surface-mounted fixture is suitable for ceiling or wall installation, both indoors and outdoors. It automatically switches to emergency mode upon detecting a main power failure.



- Certificate: UL Listed
- Standard: UL 924, NFPA 70, NFPA 101, IBC
- Feature: High brightness, addressable
- Temperature: -5°C to 45°C
- Installation: Ceiling or wall, surface mounting
- Location: Indoors and outdoors, IP65



### Main parts and material

<b>Enclosure</b>	Fire retardant ABS (UL 94 5VA rated), or steel	<b>Lamp</b>	2 x 360° adjustable heads, each with 84 x SMD 2835 LEDs, cool white
<b>Backup power</b>	Built-in rechargeable battery, 24 hours charge time, overcharge and over-discharge protection	<b>Networking</b>	RS485
<b>Accessories</b>	Universal mounting bracket (fits standard junction boxes)	<b>Others</b>	Self-test & diagnostics, manual test button, status indicator, adjustable dimming (100/50/33%)

### Available size

Type	Main power	Backup power	Duration	Luminous flux	Dimension W x H x D (mm)	Ref. No.
Intelligent waterproof non-maintained, 2 heads, ABS	100 ~ 240 VAC, 50/60 Hz, consumption 12 W	lead-acid, 12 V, 7 Ah	3 hours	1620 lm	301 x 347 x 86	CL1701 (UL)
Intelligent waterproof non-maintained, 2 heads, steel	100 ~ 240 VAC, 50/60 Hz, consumption 12 W	lead-acid, 12 V, 7 Ah	3 hours	1620 lm	301 x 347 x 86	CL1702 (UL)