

## Ceiling mount strobe (NFPA 72)

Ceiling mount strobe is a fire alarm notification appliance to provide visual alert during fire emergency, so to warn on-site personnel to take appropriate measure.



- Certificate: UL Listed / FM Approved
- Standard: UL 1638, UL 1971, NFPA 72, NFPA 70
- Feature: Field-adjustable for strobe output
- Material: ABS cover, red or white
- Temperature: 0°C to 50°C
- Humidity: 0% to 93%, non-condensing
- Installation: Indoor, ceiling mounting

### Available size

Operating voltage	Alarm current	Sound output	Strobe light	Dimension W x H x D (mm)	Enclosure color	Ref. No.
24 VDC or VFWR	226 mA @ 110 cd	/	15 / 30 / 75 / 110 cd	123 x 123 x 44	Red	A4311 (UL/FM)
24 VDC or VFWR	226 mA @ 110 cd	/	15 / 30 / 75 / 110 cd	123 x 123 x 44	White	A4312 (UL/FM)

## Wall mount strobe (NFPA 72)

Wall mount strobe is a fire alarm notification appliance to provide visual alert during fire emergency, so to warn on-site personnel to take appropriate measure.



- Certificate: UL Listed / FM Approved
- Standard: UL 1638, UL 1971, NFPA 72, NFPA 70
- Feature: Field-adjustable for strobe output
- Material: ABS cover, red or white
- Temperature: 0°C to 50°C
- Humidity: 0% to 93%, non-condensing
- Installation: Indoor, wall mounting

### Available size

Operating voltage	Alarm current	Sound output	Strobe light	Dimension W x H x D (mm)	Enclosure color	Ref. No.
24 VDC or VFWR	179 mA @ 185 cd	/	15 / 30 / 75 / 110 / 185 cd	123 x 123 x 50	Red	A4411 (UL/FM)
24 VDC or VFWR	179 mA @ 185 cd	/	15 / 30 / 75 / 110 / 185 cd	123 x 123 x 50	White	A4412 (UL/FM)