


## Self-contained maintained text-based exit sign (Metal enclosure & bilingual)

Self-contained maintained text-based exit sign (Metal enclosure & bilingual) is a continuously illuminated evacuation device installed above exit doors and along egress paths. It provides clear guidance to emergency exit, ensuring high visibility and reliable direction for occupant in low-light or smoke-obscured environments.



- Certificate: UL Listed
- Standard: UL 924, NFPA 70, NFPA 101, IBC
- Feature: High brightness, self-contained
- Temperature: -5°C to 45°C
- Installation: Ceiling or wall, surface mounting
- Location: Indoors only, IP20



### Main parts and material

|                     |   |                     |   |
|---------------------|---|---------------------|---|
| <b>Enclosure</b>    | Aluminum alloy, translucent acrylic panel   | <b>Light source</b> | LED array, up to 100 ft viewing distance                      |
| <b>Backup power</b> | Built-in rechargeable battery, 24 hours charge time, overcharge and over-discharge protection | <b>Networking</b>   | /   |
| <b>Accessories</b>  | Universal mounting bracket (fits standard junction box), removable directional arrow sticker  | <b>Others</b>       | Self-test & diagnostics, manual test button, status indicator |

### Available size

| Type   | Main power                                | Backup power             | Duration | Luminance             | Dimension W x H x D (mm) | Ref. No.    |
|--|---|--------------------------|----------|-----------------------|--------------------------|-------------|
| Single face, lettering<br>مخرج EXIT + arrow, green | 120/277 VAC, 50/60 Hz,<br>consumption 3 W | Ni-MH, 4.8 V,<br>600 mAh | 3 hours  | > 8 cd/m <sup>2</sup> | 337 x 325 x 46           | CL2201 (UL) |
| Single face, lettering<br>مخرج EXIT + arrow, red   | 120/277 VAC, 50/60 Hz,<br>consumption 3 W | Ni-MH, 4.8 V,<br>600 mAh | 3 hours  | > 8 cd/m <sup>2</sup> | 337 x 325 x 46           | CL2202 (UL) |
| Double face, lettering<br>مخرج EXIT + arrow, green | 120/277 VAC, 50/60 Hz,<br>consumption 3 W | Ni-MH, 4.8 V,<br>600 mAh | 3 hours  | > 8 cd/m <sup>2</sup> | 337 x 325 x 46           | CL2203 (UL) |
| Double face, lettering<br>مخرج EXIT + arrow, red   | 120/277 VAC, 50/60 Hz,<br>consumption 3 W | Ni-MH, 4.8 V,<br>600 mAh | 3 hours  | > 8 cd/m <sup>2</sup> | 337 x 325 x 46           | CL2204 (UL) |