

## Self-contained maintained running man exit sign (Metal enclosure)

Self-contained maintained running man exit sign (Metal enclosure) is a continuously illuminated evacuation device installed above exit doors and along egress paths. It provides clear guidance to emergency exit, ensuring high visibility and reliable direction for occupant in low-light or smoke-obscured environments.



Optional pictogram



- Certificate: UL Listed
- Standard: UL 924, NFPA 70, NFPA 101, IBC
- Feature: High brightness, self-contained
- Temperature: -5°C to 45°C
- Installation: Ceiling or wall, surface mounting
- Location: Indoors only, IP20



### Main parts and material

<b>Enclosure</b>	Aluminum alloy, translucent acrylic panel	<b>Light source</b>	LED array, up to 100 ft viewing distance
<b>Backup power</b>	Built-in rechargeable battery, 24 hours charge time, overcharge and over-discharge protection	<b>Networking</b>	/
<b>Accessories</b>	Universal mounting bracket (fits standard junction box)	<b>Others</b>	Manual test button, status indicator

### Available size

Type	Main power	Backup power	Duration	Luminance	Dimension W x H x D (mm)	Ref. No.
Single face, running man	120/277 VAC, 50/60 Hz, consumption 3 W	Ni-Cd, 4.8 V, 500 mAh	3 hours	> 8 cd/m <sup>2</sup>	310 x 227 x 46	CL2501 (UL)
Single face, running man + arrow to right	120/277 VAC, 50/60 Hz, consumption 3 W	Ni-Cd, 4.8 V, 500 mAh	3 hours	> 8 cd/m <sup>2</sup>	310 x 227 x 46	CL2502 (UL)
Single face, running man + arrow to left	120/277 VAC, 50/60 Hz, consumption 3 W	Ni-Cd, 4.8 V, 500 mAh	3 hours	> 8 cd/m <sup>2</sup>	310 x 227 x 46	CL2503 (UL)
Single face, running man + arrow to down	120/277 VAC, 50/60 Hz, consumption 3 W	Ni-Cd, 4.8 V, 500 mAh	3 hours	> 8 cd/m <sup>2</sup>	310 x 227 x 46	CL2504 (UL)

## Self-contained maintained running man exit sign (Metal enclosure)

### Available size

Type	Main power	Backup power	Duration	Luminance	Dimension W x H x D (mm)	Ref. No.
Double face, running man	120/277 VAC, 50/60 Hz, consumption 3 W	Ni-Cd, 4.8 V, 500 mAh	3 hours	> 8 cd/m <sup>2</sup>	310 x 227 x 46	CL2505 (UL)
Double face, running man + arrow to right	120/277 VAC, 50/60 Hz, consumption 3 W	Ni-Cd, 4.8 V, 500 mAh	3 hours	> 8 cd/m <sup>2</sup>	310 x 227 x 46	CL2506 (UL)
Double face, running man + arrow to left	120/277 VAC, 50/60 Hz, consumption 3 W	Ni-Cd, 4.8 V, 500 mAh	3 hours	> 8 cd/m <sup>2</sup>	310 x 227 x 46	CL2507 (UL)
Double face, running man + arrow to down	120/277 VAC, 50/60 Hz, consumption 3 W	Ni-Cd, 4.8 V, 500 mAh	3 hours	> 8 cd/m <sup>2</sup>	310 x 227 x 46	CL2508 (UL)