

Emergency exit safety sign

Emergency exit safety sign requires zero electricity. It absorbs ambient light to energize its phosphorescent material, causing the symbol to glow brightly for hours in the dark, thus ensuring reliable egress guidance during power outages.



- Certificate: ISO
- Standard: NFPA 170, ISO 7010
- Feature: Phosphor-coated PVC substrate for power-free, self-sustained illumination
- Temperature: 10°C to 40°C
- Installation: Surface mounting
- Location: Indoors only, IP20



Available size

Symbol	Luminance	Dimension W x H (mm)	Ref. No.
Right, graphic + text + arrow to right	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5301 (ISO)
Right, graphic + text + arrow to up	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5302 (ISO)
Right, graphic + text + arrow to down	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5303 (ISO)
Right, graphic + text + arrow to upper right	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5304 (ISO)
Right, graphic + text + arrow to lower right	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5305 (ISO)
Left, graphic + text + arrow to left	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5306 (ISO)
Left, graphic + text + arrow to up	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5307 (ISO)
Left, graphic + text + arrow to down	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5308 (ISO)
Left, graphic + text + arrow to upper left	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5309 (ISO)
Left, graphic + text + arrow to lower left	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5310 (ISO)
Left, graphic + arrow to left & right	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5311 (ISO)
Left, graphic + text	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5312 (ISO)
EXIT, text only	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	330 x 120	CL5313 (ISO)