

Fire extinguisher safety sign

Fire extinguisher safety sign requires zero electricity. It absorbs ambient light to energize its phosphorescent material, causing the symbol to clearly mark the location of the fire extinguisher in the dark, thus ensuring quick identification for occupants and firefighters.



- Certificate: ISO
- Standard: NFPA 170, ISO 7010
- Feature: Phosphor-coated PVC substrate for power-free, self-sustained illumination
- Temperature: 10°C to 40°C
- Installation: Surface mounting
- Location: Indoors only, Ip20

Available size

Symbol	Luminance	Dimension W x H (mm)	Ref. No.
Fire extinguisher, graphic	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	150 x 150	CL6101 (ISO)
Fire extinguisher, graphic + text	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	300 x 150	CL6102 (ISO)
Fire extinguisher, graphic + text + arrow	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	170 x 110	CL6103 (ISO)

Fire hose reel safety sign

Fire hose reel safety sign requires zero electricity. It absorbs ambient light to energize its phosphorescent material, causing the symbol to clearly mark the location of the fire hose reel in the dark, thus ensuring quick identification for occupants and firefighters.



- Certificate: ISO
- Standard: NFPA 170, ISO 7010
- Feature: Phosphor-coated PVC substrate for power-free, self-sustained illumination
- Temperature: 10°C to 40°C
- Installation: Surface mounting
- Location: Indoors only, Ip20

Available size

Symbol	Luminance	Dimension W x H (mm)	Ref. No.
Fire hose reel, graphic	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	150 x 150	CL6201 (ISO)
Fire hose reel, graphic + text + arrow	PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min	170 x 110	CL6202 (ISO)