

Fire hydrant safety sign

Fire hydrant safety sign requires zero electricity. It absorbs ambient light to energize its phosphorescent material, causing the symbol to clearly mark the location of the fire hydrant in the dark, thus ensuring quick identification for occupants and firefighters.



- Certificate: ISO
- Standard: NFPA 170, ISO 7010
- Feature: Phosphor-coated PVC substrate for power-free, self-sustained illumination
- Temperature: 10°C to 40°C
- Installation: Surface mounting
- Location: Indoors only, Ip20



Available size

| Symbol | Luminance | Dimension W x H (mm) | Ref. No. |
|--------------------------------------|---|----------------------|--------------|
| Fire hydrant, graphic | PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min | 150 x 150 | CL6301 (ISO) |
| Fire hydrant, text | PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min | 400 x 150 | CL6302 (ISO) |
| Fire hydrant, graphic + text + arrow | PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min | 170 x 110 | CL6303 (ISO) |

Fire ladder safety sign

Fire ladder safety sign requires zero electricity. It absorbs ambient light to energize its phosphorescent material, causing the symbol to clearly mark the location of the fire ladder in the dark, thus ensuring quick identification for occupants and firefighters.



- Certificate: ISO
- Standard: NFPA 170, ISO 7010
- Feature: Phosphor-coated PVC substrate for power-free, self-sustained illumination
- Temperature: 10°C to 40°C
- Installation: Surface mounting
- Location: Indoors only, Ip20

Available size

| Symbol | Luminance | Dimension W x H (mm) | Ref. No. |
|----------------------|---|----------------------|--------------|
| Fire ladder, graphic | PSPA Class C, > 140 mcd/m ² in 10 min, > 20 mcd/m ² in 60 min | 150 x 150 | CL6401 (ISO) |