

## Fire hydrant safety sign

Fire hydrant safety sign requires zero electricity. It absorbs ambient light to energize its phosphorescent material, causing the symbol to clearly mark the location of the fire hydrant in the dark, thus ensuring quick identification for occupants and firefighters.



- Certificate: ISO
- Standard: NFPA 170, ISO 7010
- Feature: Phosphor-coated PVC substrate for power-free, self-sustained illumination
- Temperature: 10°C to 40°C
- Installation: Surface mounting
- Location: Indoors only, Ip20



### Available size

Symbol	Luminance	Dimension W x H (mm)	Ref. No.
Fire hydrant, graphic	PSPA Class C, > 140 mcd/m <sup>2</sup> in 10 min, > 20 mcd/m <sup>2</sup> in 60 min	150 x 150	CL6301 (ISO)
Fire hydrant, text	PSPA Class C, > 140 mcd/m <sup>2</sup> in 10 min, > 20 mcd/m <sup>2</sup> in 60 min	400 x 150	CL6302 (ISO)
Fire hydrant, graphic + text + arrow	PSPA Class C, > 140 mcd/m <sup>2</sup> in 10 min, > 20 mcd/m <sup>2</sup> in 60 min	170 x 110	CL6303 (ISO)

## Fire ladder safety sign

Fire ladder safety sign requires zero electricity. It absorbs ambient light to energize its phosphorescent material, causing the symbol to clearly mark the location of the fire ladder in the dark, thus ensuring quick identification for occupants and firefighters.



- Certificate: ISO
- Standard: NFPA 170, ISO 7010
- Feature: Phosphor-coated PVC substrate for power-free, self-sustained illumination
- Temperature: 10°C to 40°C
- Installation: Surface mounting
- Location: Indoors only, Ip20

### Available size

Symbol	Luminance	Dimension W x H (mm)	Ref. No.
Fire ladder, graphic	PSPA Class C, > 140 mcd/m <sup>2</sup> in 10 min, > 20 mcd/m <sup>2</sup> in 60 min	150 x 150	CL6401 (ISO)