


## Self-contained waterproof non-maintained emergency luminaire (2 adjustable heads)

Self-contained waterproof non-maintained emergency luminaire (2 adjustable heads) provides customizable illumination coverage during power outages. This classic surface-mounted fixture is suitable for ceiling or wall installation, both indoors and outdoors. It automatically switches to emergency mode upon detecting a main power failure.



- Certificate: ISO
- Standard: EN IEC 60598-2-22
- Feature: High brightness, self-contained
- Temperature: -5°C to 45°C
- Installation: Ceiling or wall, surface mounting
- Location: Indoors and outdoors, IP65



### Main parts and material

<b>Enclosure</b>	Fire retardant ABS	<b>Lamp</b>	2 x 360° adjustable heads, each with 84 x SMD 2835 LEDs, cool white
<b>Backup power</b>	Built-in rechargeable battery, 24 hours charge time, overcharge and over-discharge protection	<b>Networking</b>	/
<b>Accessories</b>	Universal mounting bracket (fits standard junction boxes)	<b>Others</b>	Self-test & diagnostics, manual test button, status indicator, adjustable dimming (100/50/33%)

### Available size

Type	Main power	Backup power	Duration	Luminous flux	Dimension W x H x D (mm)	Ref. No.
Self-contained waterproof non-maintained, 2 heads	100 ~ 240 VAC, 50/60 Hz, consumption 12 W	lead-acid, 12 V, 7 Ah	3 hours	1620 lm	301 x 347 x 86	CL7501 (ISO)