

Self-contained maintained safety sign (Metal enclosure)


Self-contained maintained safety sign (Metal enclosure) is a continuously illuminated evacuation device installed above exit doors and along egress paths. It provides clear guidance to emergency exit, ensuring high visibility and reliable direction for occupant in low-light or smoke-obscured environments.



Optional pictogram



- Certificate: CE
- Standard: EN IEC 60598-2-22
- Feature: High brightness, self-contained
- Temperature: -10°C to 50°C
- Installation: Ceiling or wall, surface mounting
- Location: Indoors only, IP20



Main parts and material

Enclosure	Aluminum alloy, translucent acrylic panel	Light source	LED array, 14 x SMD 2835
Backup power	Built-in rechargeable battery, 24 hours charge time, overcharge and over-discharge protection	Networking	/
Accessories	Universal mounting bracket (fits standard junction box)	Others	Self-test & diagnostics, manual test button, status indicator

Available size

Type	Main power	Backup power	Duration	Luminance	Dimension W x H x D (mm)	Ref. No.
Double face, EXIT	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7601 (CE)
Double face, running man	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7602 (CE)
Double face, running man + arrow to right	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7603 (CE)
Double face, running man + arrow to up	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7604 (CE)

CL76 /

Self-contained maintained safety sign (Metal enclosure)

Available size

Type	Main power	Backup power	Duration	Luminance	Dimension W x H x D (mm)	Ref. No.
Double face, running man + arrow to down	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7605 (CE)
Double face, running man + EXIT + arrow to right	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7606 (CE)
Double face, running man + EXIT + arrow to up	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7607 (CE)
Double face, running man + EXIT + arrow to down	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7608 (CE)
Double face, running man + مخرج EXIT + arrow to right	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7609 (CE)
Double face, running man + مخرج EXIT + arrow to up	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7610 (CE)
Double face, running man + مخرج EXIT + arrow to down	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m ²	310 x 227 x 46	CL7611 (CE)