

## Self-contained maintained pendent safety sign (Plastic enclosure)


Self-contained maintained pendent safety sign (Plastic enclosure) is a continuously illuminated evacuation device installed above exit doors and along egress paths. It provides clear guidance to emergency exit, ensuring high visibility and reliable direction for occupant in low-light or smoke-obscured environments.



Optional pictogram



- Certificate: CE
- Standard: EN IEC 60598-2-22
- Feature: High brightness, self-contained
- Temperature: -10°C to 50°C
- Installation: Ceiling or wall, pendent mounting
- Location: Indoors only, IP20



### Main parts and material

<b>Enclosure</b>	Fire retardant ABS	<b>Light source</b>	LED array, 14 x SMD 2835
<b>Backup power</b>	Built-in rechargeable battery, 24 hours charge time, overcharge and over-discharge protection	<b>Networking</b>	/
<b>Accessories</b>	Universal mounting bracket (fits standard junction box)	<b>Others</b>	Self-test & diagnostics, manual test button, status indicator

### Available size

Type	Main power	Backup power	Duration	Luminance	Dimension W x H x D (mm)	Ref. No.
Single face, running man	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m <sup>2</sup>	320 x 600 x 60	CL7801 (CE)
Single face, running man + arrow to right	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m <sup>2</sup>	320 x 600 x 60	CL7802 (CE)
Single face, running man + arrow to left	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m <sup>2</sup>	320 x 600 x 60	CL7803 (CE)
Single face, running man + arrow to down	220 ~ 240 VAC, 50/60 Hz, consumption 3 W	Ni-MH, 4.8 V, 600 mAh	3 hours	> 8 cd/m <sup>2</sup>	320 x 600 x 60	CL7804 (CE)

CL78 /