

# Foam fire extinguisher

Fire extinguisher contains extinguishing medium which is expelled by the action of internal pressure and directed to combat a fire. For portable foam fire extinguisher, it is suitable for against Class A and B fire.



- Certificate: BSI / LPCB / CE Approved
- Standard: BS EN 3-7 / 3-8 / 3-10
- Fire rating: Class A and B fire
- Temperature: 5°C to 60°C
- W. pressure: 15 bar
- Test: 27 bar
- Surface: Red powder coating



## Main parts and material

<b>Cylinder</b>	Deep drawn steel, DC01 or DC04 to EN 10130	<b>Extinguishing medium</b>	AFFF foam
<b>Control valve</b>	Brass, with pressure indicator	<b>Hose assembly</b>	Rubber, with hose retaining clip

## Available size (Source 1 with BSI/LPCB/CE)

Capacity (kg)	BSI / LPCB rating	Dimension (mm)		Overall weight (kg)	Discharge time (sec.)	Discharge range (m)	Ref. No.
		Cylinder dia.	Height				
2	8A & 55B	110	403	3.6	15	3 ~ 5	FE8201 (BSI/LPCB/CE)
3	13A & 89B	130	438	5.2	20	3 ~ 5	FE8202 (BSI/LPCB/CE)
6	21A & 144B	162	537	9.6	22	3 ~ 5	FE8203 (BSI/LPCB/CE)
9	27A & 233B	182	620	14	30	3 ~ 5	FE8204 (BSI/LPCB/CE)

Note: Fire extinguisher bracket is included.

## Available size (Source 2 with BSI/CE)

Capacity (kg)	BSI / LPCB rating	Dimension (mm)		Overall weight (kg)	Discharge time (sec.)	Discharge range (m)	Ref. No.
		Cylinder dia.	Height				
6	13A & 113B	172	543	10	22	3 ~ 5	FE8223 (BSI/CE)
9	21A & 183B	185	620	13.6	30	3 ~ 5	FE8224 (BSI/CE)

Note: Fire extinguisher bracket is included.

**FE82/**