

Water fire extinguisher

Fire extinguisher contains extinguishing medium which is expelled by the action of internal pressure and directed to combat a fire. For portable water fire extinguisher, it is a cost effective option for Class A fire risk.



- Certificate: BSI / LPCB / CE Approved
- Standard: BS EN 3-7 / 3-8 / 3-10
- Fire rating: Class A fire
- Temperature: 5°C to 60°C
- W. pressure: 15 bar
- Test: 27 bar
- Surface: Red powder coating



Main parts and material

Cylinder	Deep drawn steel, DC01 or DC04 to EN 10130	Extinguishing medium	Water, or water additive
Control valve	Brass, with pressure indicator	Hose assembly	Rubber, with hose retaining clip

Available size (Source 1 with BSI/LPCB/CE)

Capacity (L)	Extinguishing medium	BSI / LPCB rating	Dimension (mm)		Overall weight (kg)	Discharge time (sec.)	Discharge range (m)	Ref. No.
			Cylinder dia.	Height				
3	Water+additive	13A	130	435	5.2	20	3 ~ 5	FE8301 (BSI/LPCB)
6	Water+additive	27A	162	537	9.6	45	3 ~ 5	FE8302 (BSI/LPCB)
6	Water	13A	162	537	9.6	45	3 ~ 5	FE8303 (BSI/LPCB/CE)
9	Water	21A	182	620	14	22	3 ~ 5	FE8304 (BSI/LPCB/CE)

Note: Fire extinguisher bracket is included.

Available size (Source 2 with BSI/CE)

Capacity (L)	Extinguishing medium	BSI / LPCB rating	Dimension (mm)		Overall weight (kg)	Discharge time (sec.)	Discharge range (m)	Ref. No.
			Cylinder dia.	Height				
6	Water	13A	172	543	10	45	3 ~ 5	FE8323 (BSI/CE)
9	Water	21A	185	620	13.6	22	3 ~ 5	FE8324 (BSI/CE)

Note: Fire extinguisher bracket is included.