

Grooved end cap



- Certificate: UL Listed / FM Approved
- Standard: ANSI / UL 213C
- Material: Ductile iron ASTM A536, 65-45-12
Stainless steel ASTM A312 304 / 316
- Rated pressure: 300 ~ 500 psi
- Surface: Red painting / hot dip galvanized
SS 304 / SS 316



Available size

Size			End to end	Ref. No.
Inch	DN	mm	L (mm)	
1"	25	33.7	22	G4001 (UL/FM)
1-1/4"	32	42.4	24	G4002 (UL/FM)
1-1/2"	40	48.3	24	G4003 (UL/FM)
2"	50	60.3	24	G4004 (UL/FM)
2-1/2"	65	73.0	24	G4005 (UL/FM)
2-1/2"	65	76.1	24	G4006 (UL/FM)
3"	80	88.9	24	G4007 (UL/FM)
4"	100	114.3	27	G4008 (UL/FM)
5"	125	139.7	27	G4009 (UL/FM)
5"	125	141.3	27	G4010 (UL/FM)
6"	150	165.1	27	G4011 (UL/FM)
6"	150	168.3	27	G4012 (UL/FM)
8"	200	219.1	30	G4013 (UL/FM)
10"	250	273.0	32	G4014 (UL/FM)
12"	300	323.9	32	G4015 (UL/FM)
14"	350	355.6	165	G4016 (UL)