

CPVC socket 90° elbow



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC, inherently flame-retardant
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
3/4"	20	26.7	Sch40 / Sch80	Socket	175	PL4201 (UL/FM)
1"	25	33.4	Sch40 / Sch80	Socket	175	PL4202 (UL/FM)
1-1/4"	32	42.2	Sch40 / Sch80	Socket	175	PL4203 (UL/FM)
1-1/2"	40	48.3	Sch40 / Sch80	Socket	175	PL4204 (UL/FM)
2"	50	60.3	Sch40 / Sch80	Socket	175	PL4205 (UL/FM)
2-1/2"	65	73.0	Sch40 / Sch80	Socket	175	PL4206 (UL/FM)
3"	80	88.9	Sch40 / Sch80	Socket	175	PL4207 (UL/FM)

CPVC socket 90° reducing elbow



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC, inherently flame-retardant
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
1" x 3/4"	25 x 20	33.4 x 26.7	Sch40 / Sch80	Socket	175	PL4301 (UL/FM)
1-1/4" x 1"	32 x 25	42.2 x 33.4	Sch40 / Sch80	Socket	175	PL4302 (ISO)