

## CPVC socket straight cross (equal cross)



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC, inherently flame-retardant
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)

### Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
3/4"	20	26.7	Sch40 / Sch80	Socket	175	PL4701 (UL/FM)
1"	25	33.4	Sch40 / Sch80	Socket	175	PL4702 (UL/FM)
1-1/4"	32	42.2	Sch40 / Sch80	Socket	175	PL4703 (UL/FM)
1-1/2"	40	48.3	Sch40 / Sch80	Socket	175	PL4704 (UL/FM)
2"	50	60.3	Sch40 / Sch80	Socket	175	PL4705 (UL/FM)
2-1/2"	65	73.0	Sch40 / Sch80	Socket	175	PL4706 (UL/FM)
3"	80	88.9	Sch40 / Sch80	Socket	175	PL4707 (UL/FM)

## CPVC socket cap



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC, inherently flame-retardant
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)

### Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
3/4"	20	26.7	Sch40 / Sch80	Socket	175	PL4801 (UL/FM)
1"	25	33.4	Sch40 / Sch80	Socket	175	PL4802 (UL/FM)
1-1/4"	32	42.2	Sch40 / Sch80	Socket	175	PL4803 (UL/FM)
1-1/2"	40	48.3	Sch40 / Sch80	Socket	175	PL4804 (UL/FM)
2"	50	60.3	Sch40 / Sch80	Socket	175	PL4805 (UL/FM)
2-1/2"	65	73.0	Sch40 / Sch80	Socket	175	PL4806 (UL/FM)
3"	80	88.9	Sch40 / Sch80	Socket	175	PL4807 (UL/FM)