

## CPVC socket reducing coupling



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC, inherently flame-retardant
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



### Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
1" x 3/4"	25 x 20	33.4 x 26.7	Sch40 / Sch80	Socket	175	PL5301 (UL/FM)
1-1/4" x 1"	32 x 25	42.2 x 33.4	Sch40 / Sch80	Socket	175	PL5302 (UL/FM)
1-1/4" x 3/4"	32 x 20	42.2 x 26.7	Sch40 / Sch80	Socket	175	PL5303 (UL/FM)
1-1/2" x 1-1/4"	40 x 32	48.3 x 42.2	Sch40 / Sch80	Socket	175	PL5304 (UL/FM)
1-1/2" x 1"	40 x 25	48.3 x 33.4	Sch40 / Sch80	Socket	175	PL5305 (UL/FM)
1-1/2" x 3/4"	40 x 20	48.3 x 26.7	Sch40 / Sch80	Socket	175	PL5306 (UL/FM)
2" x 1-1/2"	50 x 40	60.3 x 48.3	Sch40 / Sch80	Socket	175	PL5307 (UL/FM)
2" x 1-1/4"	50 x 32	60.3 x 42.2	Sch40 / Sch80	Socket	175	PL5308 (UL/FM)
2" x 1"	50 x 25	60.3 x 33.4	Sch40 / Sch80	Socket	175	PL5309 (UL/FM)
2" x 3/4"	50 x 20	60.3 x 26.7	Sch40 / Sch80	Socket	175	PL5310 (UL/FM)